TYPE 27
Specialty Wheels

Cutting/Grinding
1/8"

A24R Pipeline - Long Life

- Aluminum oxide grain
- For the pipeline industry
- **Designed and manufactured to perform both cutting and light grinding**
- Long life

METAL Ferrous metals (steel, cast iron, etc.)




A24 Turbo - High Performance

- Aluminum oxide grain
- For the pipeline industry
- **High performance cutting, notching and light grinding**
- Long life

METAL Ferrous metals (steel, cast iron, etc.)





Size			Max	Part Number		Qty Per	Qty Per	Lbs Per
A Dia.	B Width	C Bore	RPM	Pipeline	Turbo	Box	Ctn	Box
3	1/8	3/8	18,000	22005	-	25	100	2
4	1/8	3/8	13,500	22007	-	25	100	3
4	1/8	5/8	13,500	22015	-	25	100	3
4-1/2	1/8	7/8	13,300	22030	23703	25	100	7
4-1/2	1/8	5/8-11	13,300	22130	23713	10	40	5
5	1/8	7/8	12,200	22040	23705	25	100	6
5	1/8	5/8-11	12,200	22140	23715	10	40	5
6	1/8	7/8	10,200	22042	23706	25	50	10
6	1/8	5/8-11	10,200	22046	23716	10	40	7
7	1/8	7/8	8,500	22055	23707	25	50	14
7	1/8	5/8-11	8,500	22052	23717	10	40	9
9	1/8	7/8	6,600	22065	-	25	50	22
9	1/8	5/8-11	6,600	22062	-	10	40	12


5/8-11 Super-Lock™ Hub


Angle Grinder

Note: Reusable 5/8-11 adaptor for use on Type 1 and Type 27 reinforced wheels with a 7/8 arbor, a max. diameter of 5" and a wheel thickness of .045 to 1/8" available on page 153 (part #95055). Part numbers 23713 and 23715 do not use Super-Lock™ Hub.

Tech INFO

- Only wheel designed for both cutting and light grinding, eliminating the need for 2 separate wheels
- General purpose formulation provides optimum performance over a wide range of applications
- All sizes reinforced with the highest quality fiberglass for maximum safety and performance
- Super-Lock™ Hub on all 5/8-11 threaded wheels is the safest, vibration-free design