



ASME B18.2.6 2003

Bolt Diameter	<u>D</u>	<u>F</u>				<u>C</u>		<u>H</u>			<u>I</u>
	Body Diameter	Width Across Flats			Width Across Corners		Height			Thread Length	
	Max	Basic	Max	Min	Max	Min	Basic	Max	Min	Basic	
1/2	0.515	7/8	0.875	0.85	1.01	0.969	5/16	0.323	0.302	1	
5/8	0.642	1 1/16	1.062	1.031	1.227	1.175	25/64	0.403	0.378	1.25	
3/4	0.768	1 1/4	1.25	1.212	1.443	1.383	15/32	0.483	0.455	1.38	
7/8	0.895	1 7/16	1.438	1.394	1.66	1.589	35/64	0.563	0.531	1.5	
1	1.022	1 5/8	1.625	1.575	1.876	1.796	39/64	0.627	0.591	1.75	
1 1/8	1.149	1 13/16	1.812	1.756	2.093	2.002	11/16	0.718	0.658	2	
1 1/4	1.277	2	2	1.938	2.309	2.209	25/32	0.813	0.749	2	
1 3/8	1.404	2 3/16	2.188	2.119	2.526	2.416	27/32	0.878	0.81	2.25	
1 1/2	1.531	2 3/8	2.375	2.3	2.742	2.622	15/16	0.974	0.902	2.25	