



ROUND HEAD SCREWS

MACHINE SCREWS WOOD SCREWS



Nominal Size	A		H		J		T		G				Phillips Driver Size
	Head Diameter		Height of Head		Width of Slot		Depth of Slot		Dimensions of Recess				
	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	
2	.162	.146	.069	.059	.031	.023	.048	.037	.100	.087	.053	.017	1
3	.187	.169	.078	.067	.035	.027	.053	.040	.109	.096	.062	.018	1
4	.211	.193	.086	.075	.039	.031	.058	.044	.118	.105	.072	.019	1
5	.236	.217	.095	.083	.043	.035	.063	.047	.154	.141	.074	.027	2
6	.260	.240	.103	.091	.048	.039	.068	.051	.162	.149	.084	.027	2
7*	.285	.264	.111	.099	.048	.039	.072	.055	.170	.157	.092	.029	2
8	.309	.287	.120	.107	.054	.045	.077	.058	.178	.165	.101	.030	2
9*	.334	.311	.128	.115	.054	.045	.082	.062	.186	.173	.110	.030	2
10	.359	.334	.137	.123	.060	.050	.087	.065	.195	.182	.119	.031	2-3*
12	.408	.382	.153	.139	.067	.056	.096	.072	.249	.236	.125	.032	3
14*	.457	.429	.170	.155	.075	.064	.106	.080	.265	.252	.142	.034	3
1/4	.472	.443	.175	.160	.075	.064	.109	.082	.268	.255	.147	.034	3
5/16	.590	.557	.216	.198	.084	.072	.132	.099	-	-	-	-	-
3/8	.708	.670	.256	.237	.094	.081	.155	.117	-	-	-	-	-
1/2	.813	.766	.355	.332	.106	.091	.211	.159	-	-	-	-	-

ASME B18.6.3

